



Version 1.0, Mar 1, 2007

WiMAX MBS Architecture

Professor: Taekyoung Kwon

Students: Hojin Lee, Jihoon Lee, and Bokgyun Jeon

Multimedia and Mobile Communication Laboratory

Seoul National University

Contents

1		
2		
3	1 Introduction and Scope	7
4	2 Abbreviations and Acronyms	7
5	3 References	8
6	4 Definitions.....	10
7	4.1 Multicast Group.....	10
8	4.2 MBS Channel	10
9	4.3 MBS Program.....	10
10	4.3.1 Broadcast Program.....	10
11	4.3.2 Multicast Program	10
12	4.4 MBS Session.....	10
13	4.5 MBS Zone	11
14	4.6 MBS Controller	11
15	5 Reference Model.....	12
16	5.1 MBS Source.....	12
17	5.2 MBSC.....	12
18	5.2.1 Service Announcement Function.....	12
19	5.2.2 Membership Management Function	12
20	5.2.3 Security Function.....	12
21	5.2.4 Session Management and Transmission Function	13
22	5.3 ASN-GW	13
23	5.3.1 MR (Multicast Router)	13
24	5.3.2 MBS-F	13
25	5.4 BS	14
26	5.4.1 Scheduling Function	14
27	5.4.2 IEEE 802.16 MBS Transmission Function.....	14
28	5.4.3 Service Flow Management Function	14
29	5.5 MS	15
30	5.5.1 Service Discovery Function.....	15
31	5.5.2 Service Subscription Function	15
32	5.5.3 Service Flow Management Function	15
33	5.5.4 IEEE 802.16 MBS Reception Function.....	15
34	5.6 Reference Points.....	15
35	5.6.1 R1	15
36	5.6.2 R2	15

1	5.6.3 R3	16
2	5.6.4 R4	16
3	5.6.5 R6	16
4	6 Flows	17
5	6.1 Initial Proposal for MBS Service Flow.....	17
6	6.1.1 Service Discovery and Announcement.....	17
7	6.1.2 Service Subscription	18
8	6.1.3 Joining	18
9	6.1.4 Session Start	21
10	6.1.5 Data Transfer	21
11	6.1.6 Leaving.....	21
12	6.1.7 Session Stop.....	22
13	6.2 Harmonized Proposal for MBS Service Flow	23
14	6.2.1 MBS Controller discovery	23
15	6.2.2 Service discovery and announcement.....	23
16	6.2.3 MBS Subscription.....	24
17	6.2.4 Joining	24
18	6.2.5 Leave	28
19	7 Channel Zapping Delay.....	35
20	7.1 Definition of Channel Zapping Delay.....	35
21	7.2 Methods to Reduce the Delay of Multicast Tree Construction.....	35
22	7.2.1 Assumptions	35
23	7.2.2 Delayed IP multicast leave	35
24	7.2.3 Unsolicited IP multicast join.....	35
25	7.3 Methods to Reduce the MBS signaling delay.....	35
26	8 Security	36
27	8.1 MBS AAA Security.....	36
28	8.2 MBS security Architecture	36
29	9 MBS Zone Management.....	38
30	9.1 MBS Zone	38
31	9.2 MBS Zone Planning and Traffic.....	39
32	9.3 Tracking the Locations of MSs.....	40
33	9.4 PG-based MBS	40
34	9.5 Intra-PG Handover	41
35	9.6 Inter-PG Handover	41
36	9.7 Delay Comparison	42
37	10 Scheduling.....	43

1	10.1 Requirements	43
2	10.2 CINR Feedback	43
3	10.2.1 REP-RSP MAC Message.....	43
4	10.2.2 Bandwidth Request Header with CINR Report	43
5	10.2.3 Fast Feedback (CQICH) Channel	44
6	10.3 Rate Adaptation in MBS service	44
7	10.4 Simulations	45
8	10.4.1 Environments.....	46
9	10.4.2 Results	47
10	Appendix A 3GPP MBMS Architecture.....	49
11	A.1 Reference Architecture Model.....	49
12	A.2 Phases of MBMS Multicast Service Provision.....	49
13	A.3 MBMS Procedures.....	49
14	A.3.1 MBMS Multicast Service Activation.....	49
15	Appendix B 3GPP2 BCMCS Architecture Model	52
16	B.1 Terminology	52
17	B.2 BCMCS Architecture Model	52
18	B.3 BCMCS Controller Requirements	53
19	B.4 Overview of BCMCS Service Flow	53
20	B.4.1 Service Discovery/Announcement.....	53
21	B.4.2 Content Subscription.....	54
22	B.4.3 BCMCS Controller Discovery.....	54
23	B.4.4 BCMCS Information Acquisition	54
24	B.4.5 Content Available Determination	54
25	B.4.6 BCMCS Registration and Ran Session Discovery (RSD)	55
26	B.4.7 BCMCS Session Discovery	56
27	B.4.8 BCMCS Content Delivery	57
28	B.4.9 BCMCS de-registration	57
29	Appendix C OMA Reference Model	59
30	C.1 BCAST Functions and Protocol Stack.....	59
31	C.2 BCAST Architectural Diagram	59
32	Appendix D Installation of NS-2 simulation	62
33		
34	Figures	
35	Figure 4-1 An illustration of MBS service model.	10
36	Figure 4-2 An illustration of WiMAX MBS zone configuration.....	11

1	Figure 5-1 Network reference model.....	12
2	Figure 5-2 BS functional structure.....	14
3	Figure 5-3 MS functional structure.....	15
4	Figure 6-1 Overview of MBS Service Flow	17
5	Figure 6-2 Service Discovery and Announcement	18
6	Figure 6-3 Service Subscription	18
7	Figure 6-4 Joining.....	19
8	Figure 6-5 Session Start.....	21
9	Figure 6-6 Data Transfer	21
10	Figure 6-7 Leaving	22
11	Figure 6-8 Session Stop.....	22
12	Figure 6-9 Phases of MBS service flow provision	23
13	Figure 6-10 MBSC discovery and Service announcement	24
14	Figure 6-11 Multicast group join procedure	25
15	Figure 6-12 Service flow creation and Data path set up	27
16	Figure 6-13 Leave procedure for Scenario 1	29
17	Figure 6-14 Leave procedure for Scenario 2	31
18	Figure 6-15 Network initiated Leave.....	33
19	Figure 7-1 MBS security architecture.....	36
20	Figure 7-2 Authentication relay protocol.....	37
21	Figure 7-3 MBS authentication and authorization procedures	37
22	Figure 9-1. An illustration of MBS Join	38
23	Figure 9-2. Intra-MBS zone handover.....	39
24	Figure 9-3. PG-based MBS.....	41
25	Figure 9-4. Inter-PG Handover.....	41
26	Figure 10-1 CINR report with REP-RSP MAC message	43
27	Figure 10-2 CINR report in the bandwidth request MAC message.....	44
28	Figure 10-3 Periodically CINR report with fast-feedback (CQICH) channel	44
29	Figure 10-4 Rate adaptation MBS data scheduling	45
30	Figure 10-5 MBS data scheduling example.....	45
31	Figure 11-1 Bandwidth occupancy comparison rate adaptation schem with using fixed rate scheme	47
32	Figure 11-2 Delivery ratio using rate adaptation scheme	48
33	Figure A-1 Reference Architecture Model	49
34	Figure A-2 Phases of Multicast Service Provision	49
35	Figure A-3 MBMS Service Activation.....	50
36	Figure B-1 High level view: Broadcast/Multicast Service	52
37	Figure B-2 BCMCS Architecture model in 3G cellular network	53

1 Figure B-3 BCMCS Service Flow 53

2 Figure B-4 BCMCS Information Acquisition Flow 54

3 Figure B-5 BCMCS Registration and RSD Call Flow (1x System) 55

4 Figure B-6 A8/A10 Establishment - Initiated by the BS/AN 56

5 Figure B-7 A8/A10 Establishment (A10 established) - Initiated by the BS/AN 56

6 Figure B-8 BSN Session Discovery Call Flow 57

7 Figure B-9 A8/A10 Release - Initiated by the BS/AN 57

8 Figure B-10 A8/A10 Release - Initiated by the BSN 58

9 Figure C-1 BCAST Functions and Protocol Stack 59

10 Figure C-2 BCAST Functional Architecture Diagram 59

11

Tables

12

13 Table 2-1 Abbreviations and Acronyms 7

14 Table 6-1 New Messages 17

15 Table 6-2 Message parameters – 3b. Authorization Request 19

16 Table 6-3 Message parameters – 3c. Authorization Response 20

17 Table 6-4 Message parameters – 3d. Session Info Request 20

18 Table 6-5 Message parameters – 3e. Session Info Response 20

19 Table 6-6 Message parameters – 3f. Resource Reservation Request 20

20 Table 6-7 Message parameters – 6b. Resource Reservation Request 22

21 Table 9-1. Comparison between MBS handovers in WiMAX 42

22 Table C-1 Logical Entities 60

23 Table C-2 Reference Points 61

24

1 Introduction and Scope

The rapid deployment of broadband wireless networks is raising expectation of new applications over the air interface especially in mobile environments. One of killer applications will be multimedia streaming. When many users want to receive the same multimedia service (e.g. news, live sports) at the same time, even high bandwidth wireless link resources might run into shortage if we use a point-to-point for each user.

Recently, a new kind of broadband wireless networks is emerging, IEEE 802.16 and IEEE 802.16e standards [1], [2]. The former defines the fixed broadband wireless access network and the latter augments the former for mobile communications by introducing handoff, sleep/idle mode, and multicast/broadcast service (MBS). As these specifications deal with only the air interface, another industrial forum is launched to facilitate service environments and to promote interoperability, Worldwide Interoperability for Microwave Access (WiMAX) [4].

This document describes the architecture reference model, reference points and protocols and procedures for WiMAX MBS.

2 Abbreviations and Acronyms

The following table lists several abbreviations and acronyms used throughout this document.

Table 2-1 Abbreviations and Acronyms

ABBREVIATION	EXPANSION
3GPP	Third Generation Partnership Project
3GPP2	Third Generation Partnership Project 2
ACR	Access Control Router
ASN	Access Service Network (WiMAX)
ASN-GW	Access Service Network Gateway (WiMAX)
BCAST	Mobile Broadcast Service (OMA)
BCMCS	Broadcast/Multicast Service (3GPP2)
BS	Base Station
CID	Connection Identifier
CSN	Connectivity Service Network (WiMAX)
DSA	Dynamic Service Addition
DSD	Dynamic Service Deletion
HO	Handoff
IEEE	Institute of Electrical and Electronics Engineers
IGMP	Internet Group Management Protocol
IPv4	Internet Protocol Version 4
IPv6	Internet Protocol Version 6
MAC	Medium Access Control
MBMS	Multimedia Broadcast/Multicast Service (3GPP)
MBS	Multicast Broadcast Service
MBSC	Multicast Broadcast Service Controller

MCBCS	Multicast and Broadcast Service (WiMAX)
MCID	Multicast Connection Identifier
MS	Mobile Station
NSP	Network Service Provider
OAM	Operations and Maintenance
OMA	Open Mobile Alliance
PIM-SM	Protocol Independent Multicast Sparse Mode
PIM-SSM	Protocol Independent Multicast Source Specific Multicast
PSS	Portable Subscriber Station
RAS	Radio Access Station
SFA	Service Flow Authorization
WiBro	Wireless Broadband network
WiMAX	Worldwide Interoperability for Microwave Access Forum

1

2 3 References

- 3 [1] "IEEE Standard for Local and Metropolitan Area Networks", (*IEEE Std. 802.16-2004*).
- 4 [2] "IEEE Standard for Local and Metropolitan Area Networks", (*IEEE Std. 802.16e-2005*).
- 5 [3] "Specifications for 2.3GHz band Portable Internet Service," (*TTAS.KO-06.0082*), TTA, June 2005.
- 6 [4] "WiMAX End-to-End Network Systems Architecture (Stage 2: Architecture Tenets, Reference
7 Model and Reference Points)," WiMax Forum Network Working Group (NWG), under revision,
8 www.wimaxforum.org/technology/documents/, April 2006.
- 9 [5] "WiMAX End-to-End Network Systems Architecture (Stage 3: Detailed Protocols and
10 Procedures)," WiMax Forum Network Working Group (NWG), under revision,
11 www.wimaxforum.org/technology/documents/, August 2006.
- 12 [6] "Multimedia Broadcast/Multicast Service (MBMS); Architecture and functional description
13 (Release 6)," (*3GPP TS 23.246 v6.9.0*), December 2005.
- 14 [7] "Interoperability Specification (IOS) for Broadcast Multicast Services (BCMCS)," (*A.S0019-0 v2.0*),
15 3GPP2, January 2006.
- 16 [8] "Broadcast/Multicast Services – Stage 1 Revision A," (*S.R0030-A v1.0*), 3GPP2, January 2004.
- 17 [9] "Broadcast-Multicast Service Security Framework," (*S.S0083-A v1.0*), 3GPP2, August 2004.
- 18 [10] "Mobile Broadcast Service Architecture," (*OMA-AD-BCAST-V1_0-20060329-D*), Open Mobile
19 Alliance, March 2006.
- 20 [11] "Proposed Stage 1 Requirements for MCBCS Requirements,"
21 (*060404_SPWG_MCBCS_Requirements for Rel1dot5_r1*) Service Provider Working Group, WiMAX
22 Forum, April 2006.
- 23 [12] B. Cain, S. Deering, I. Kouvelas, B. Fenner, and A. Thyagarajan, "Internet Group Management
24 Protocol, Version 3," *RFC 3376*, Oct. 2002.

- 1 [13] B. Fenner, M. Handley, H. Holbrook, and I. Kouvelas, "Protocol Independent Multicast - Sparse
- 2 Mode (PIM-SM): Protocol Specification (Revised)," *RFC 4601*, Aug 2006.
- 3 [14] S. Bhattacharyya, "An Overview of Source-Specific Multicast (SSM)," *RFC 3569*, July 2003.
- 4 [15] <http://www.antd.nist.gov/seamlessandsecure/toolsuite.html>, IEEE 802.16 model for NS-2, NIST,
- 5 Oct 2006.